

Description

[IRON GOLF CLUB (Corporate Docket Number PU2153)]

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation-in-part of co-pending U.S. Patent Application No. 10/065,147, filed on September 20, 2002.

FEDERAL RESEARCH STATEMENT

[0002] [Not Applicable]

BACKGROUND OF INVENTION

[0003] Field of the Invention

[0004] The present invention relates to an iron golf club. More specifically, the present invention relates to a multiple material iron golf club.

[0005] Description of the Related Art

[0006] Irons are typically composed of a stainless steel or titanium material, and are typically cast or forged. Most

golfers desire that their irons have a large sweet spot for greater forgiveness, a low center of gravity to get the ball in the air, a solid sound, reduced vibrations during impact, and a trim top line for appearance. Unfortunately, these desires are often in conflict with each other as it pertains to an iron.

[0007] The use of iron club heads composed of different materials has allowed some prior art irons to achieve some of these desires.

[0008] One example is U.S. Patent Number 5,228,694 to Okumoto et al., which discloses an iron club head composed of a stainless steel sole and hosel, a core composed of a bulk molding compound or the like, a weight composed of a tungsten and polyamide resin, and an outer-shell composed of a fiber-reinforced resin.

[0009] Another example is set forth in U.S. Patent Numbers 4,792,139, 4,798,383, and 4,884,812, all to Nagasaki et al., which disclose an iron club head composed of stainless steel with a fiber reinforced plastic back plate to allow for weight adjustment and ideal inertia moment adjustment.

[0010] Another example is U.S. Patent Number 4,848,747 to Fujimura et al., which discloses a metal iron club head with a

carbon fiber reinforced plastic back plate to increase the sweet spot. A ring is used to fix the position of the back plate.

[0011] Another example is set forth in U.S. Patent Numbers 4,928,972 and 4,964,640 to Nakanishi et al., which disclose an iron club head composed of stainless steel with a fiber reinforcement in a rear recess to provide a dampening means for shock and vibrations, a means for increasing the inertial moment, a means for adjusting the center of gravity and a means for reinforcing the back plate.

[0012] Another example is U.S. Patent Number 5,190,290 to Take, which discloses an iron club head with a metal body, a filling member composed of a light weight material such as a plastic, and a fiber-reinforced resin molded on the metal body and the filling member.

[0013] Another example is U.S. Patent Number 5,411,264 to Oku, which discloses a metal body with a backwardly extended flange and an elastic fiber face plate in order to increase the moment of inertia and minimize head vibrations.

[0014] Another example is U.S. Patent Number 5,472,201 to Aizawa et al., which discloses an iron club head with a body composed of stainless steel, a face member composed of a fiber reinforced resin and a protective layer

composed of a metal, in order to provide a deep center of gravity and reduce shocks.

[0015] Another example is U.S. Patent Number 5,326,106 to Meyer, which discloses an iron golf club head with a metal blade portion and hosel composed of a lightweight material such as a fiber reinforced resin.

[0016] Another example is U.S. Patent Number 4,664,383 to Aizawa et al., which discloses an iron golf club head with a metal core covered with multiple layers of a reinforced synthetic resin in order to provide greater ball hitting distance.

[0017] Another example is U.S. Patent Number 4,667,963 to Yoneyama, which discloses an iron golf club head with a metal sole and a filling member composed of a fiber reinforced resins material in order to provide greater hitting distance.

[0018] The prior art fails to disclose an iron golf club head that is composed of multiple materials, has a low center of gravity, reduced vibrations, and a greater moment of inertia.

SUMMARY OF INVENTION

[0019] The present invention provides an iron golf club head which has a low center of gravity, a high moment of inertia, reduced vibrations and a solid feel and appearance.

The present invention is able to provide these features through use of a multiple material iron club head.

[0020] One aspect of the present invention is an iron golf club head composed of a periphery member, a central member and a face plate. The periphery member is composed of a first metal material. The periphery member has a sole wall, a toe wall extending upward from the sole wall at a first end of the sole wall, a hosel extending upward from the sole wall at a second end of the sole wall, and a heel wall extending upward from the sole wall. The central member, which is coupled to the periphery member, is composed of a non-metal material. The central member has a body portion with a forward surface, a rear surface, a sole surface, a top surface, a toe surface, a heel surface. The central member has a cavity formed in the rear surface of the body portion. The face plate is composed of a second metal material, which has a lower density than the first metal material. The face plate is coupled to the periphery member and is disposed over the forward surface of the central member.

[0021] Another aspect of the invention is an iron golf club including a periphery member, a central member and a face plate. The periphery member is composed of a first metal

material having a density between 8 g/cm^3 and 12 g/cm^3 . The periphery member includes a sole wall, a toe wall, a hosel, a heel wall, and a top wall, the top, sole, heel and toe walls defining an opening. The central member and the face plate are disposed in the opening of the periphery member, with the face plate being disposed over the forward surface of the central member. The face plate has a thickness between 0.040 inch and 0.250 inch.

[0022] Having briefly described the present invention, the above and further objects, features and advantages thereof will be recognized by those skilled in the pertinent art from the following detailed description of the invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

[0023] FIG. 1 is an exploded view of an iron club head according to a first embodiment of the present invention.

[0024] FIG. 2 is a side exploded view of the iron club head of FIG. 1.

[0025] FIG. 3 is a front plan view of the iron club head of FIG. 1.

[0026] FIG. 4 is a rear plan view of the iron club head of FIG. 1.

[0027] FIG. 5 is a toe side view of the iron club head of FIG. 1.

[0028] FIG. 6 is a heel side view of the iron club head of FIG. 1.

[0029] FIG. 7 is a top plan view of the iron club head of FIG. 1.

[0030] FIG. 8 is a bottom plan view of the iron club head of FIG. 1.

[0031] FIG. 9 is a toe side view of a golf club head of the present invention illustrating the moments of inertia through the center of gravity.

[0032] FIG. 10 is a top plan view of a golf club head of the present invention illustrating the moments of inertia through the center of gravity.

[0033] FIG. 11 is a front plan view of a golf club head of the present invention illustrating the moments of inertia through the center of gravity.

[0034] FIG. 12 is a front perspective view of a golf club head of the present invention illustrating the moments of inertia through the center of gravity.

[0035] FIG. 13 is an exploded, front perspective view of an iron club head according to a second embodiment of the present invention.

[0036] FIG. 14 is an exploded, rear perspective view of the iron club head of FIG. 13.

[0037] FIG. 15 is a rear plan view of the iron club head of FIG. 13.

[0038] FIG. 16 is a top plan view of the iron club head of FIG. 13.

[0039] FIG. 17 is a bottom plan view of the iron club head of FIG. 13.

[0040] FIG. 18 is a front plan view of the iron club head of FIG. 13.

[0041] FIG. 19 is a toe side view of the iron club head of FIG. 13.

[0042] FIG. 20 is a heel side view of the iron club head of FIG. 13.

DETAILED DESCRIPTION

[0043] As shown in FIGS. 1–8, an iron golf club head in accordance with a first embodiment of the present invention is generally designated 20. The club head 20 is preferably composed of three main components: a periphery member 22, a central member 24 and a face plate 26. The club head 20 can range from a 1-iron to a lob-wedge, with the loft angle preferably ranging from fifteen degrees to sixty degrees. The three main components are assembled into the club head 20 using a process such as disclosed in co-pending U.S. Patent Application Number 10/065,150, filed on September 20, 2002, entitled Method For Manufacturing Iron Golf Club Head, which is hereby incorporated by reference in its entirety.

[0044] The periphery member 22 is preferably composed of a material having a density greater than 7.86 grams per

centimeter cubed ("g/cm³"). A preferred material is an iron–nickel–tungsten alloy having a density preferably ranging from 8.0 g/cm³ to 12.0 g/cm³, more preferably ranging from 9.0 g/cm³ to 10.5 g/cm³. Another preferred material is a nickel–tungsten alloy disclosed in co-pending U.S. Patent Application Number 10/604,158, filed on July 28, 2003, entitled High Density Alloy for Improved Mass Properties of an Article, which is hereby incorporated by reference in its entirety. The preferred nickel–tungsten alloy includes at least 50 weight percent nickel, at least 20 weight percent tungsten and at least 20 weight percent chromium and has a density in the range of 9.0 g/cm³ to 10.5 g/cm³. Another alternative material is a stainless steel material. Still another material is disclosed in U.S. Patent No. 6,277,326, entitled Process for Liquid–Phase Sintering of a Multiple–Component Material, which is hereby incorporated by reference in its entirety. Those skilled in the pertinent art will recognize that still other materials may be used for the periphery member 22 without departing from the scope and spirit of the present invention.

[0045] The periphery member 22 has a sole wall 28, a toe wall 30 extending upward from a toe end of the sole wall 28, a

heel wall 32 extending upward from the sole wall 28 near a heel end of the sole wall 28, and a hosel 34 extending outward from the sole wall 28 at the heel end of the sole wall 28. The hosel 34 is preferably offset. The hosel 34 has a bore 36 for receiving a shaft, and the upper end of the hosel 34 preferably lies below an upper end of the toe wall 30 when the club head 20 is in the address position for striking a golf ball, not shown. The bore 36 preferably extends through the entire hosel 34 providing a short straight hollow hosel such as disclosed in U.S. Patent Number 4,995,609, which pertinent parts are hereby incorporated by reference.

[0046] The sole wall 28 preferably has a cambered exterior surface, which contacts the ground during a golf swing. As shown in FIG. 8, the sole wall 28 has a width, " W_s ", that preferably ranges from 1.00 inch to 1.75 inch, and is most preferably 1.25 inch. The sole wall 28 also has a length, " L_s ", from a toe end to the beginning of the bore 36, which preferably ranges from 2.5 inches to 3.5 inches, and is most preferably 3.0 inches.

[0047] As shown in FIG. 5, the toe wall 30 preferably has a length, " L_T ", which preferably ranges from 1.5 inches to 2.5 inches, and is most preferably 2.0 inches. The toe wall

30 preferably has a width that tapers from a lower end to an upper end of the toe wall 30.

[0048] As shown in FIG. 6, the heel wall 32 preferably has a length, " L_H ", which preferably ranges from 0.5 inch to 1.5 inches, and is most preferably 1.0 inch. The heel wall 32 preferably has a width that tapers from a lower end to an upper end of the heel wall 32.

[0049] In general, the periphery member 22 provides the club head 20 with a greater moment of inertia due to its relatively large mass along the periphery of the club head 20. Further, mass attributable to the sole wall 28 lowers the center of gravity of the club head 20 to promote a higher trajectory during ball striking. The periphery member 22 is preferably 15% to 50% of the volume of the club head 20 and preferably 50% to 80% of the mass of the club head 20.

[0050] The central member 24 is composed of a non-metal material. Preferred materials include bulk molding compounds, sheet molding compounds, thermosetting materials and thermoplastic materials. A preferred bulk molding compound is a resinous material with reinforcement fibers. Such resins include polyesters, vinyl esters and epoxy. Such fibers include carbon fibers, fiberglass,

aramid or combinations. A preferred sheet molding compound is similar to the bulk molding compounds, however, in a sheet form. A preferred thermoplastic material includes injection moldable materials integrated with fibers such as disclosed above. These thermoplastic materials include polyesters, polyethylenes, polyamides, polypropylenes, polyurethanes, and the like.

[0051] The central member 24 is primarily a support for the face plate 26, and thus the central member should be able to withstand impact forces without failure. The central member 24 also reduces vibrations of the club head 20 during ball striking. The central member 24 is preferably 25% to 75% of the volume of the club head 20 and preferably 10% to 30% of the mass of the club head 20.

[0052] The central member 24 preferably has a body portion 38, a recess 40, a forward surface 42, a rear surface 43, a sole surface 44, a top surface 46, a toe surface 48, a heel surface 50 and a flange 52. The forward surface 42 is preferably at an angle approximate that of the club head 20. Thus, if the club head 20 is a 5-iron, then the forward surface preferably has an angle of approximately 27 degrees. The body portion 38 preferably tapers upward from the sole surface 44.

[0053] The central member 24 is disposed on an interior surface of the sole wall 28 of the periphery member 22. The toe surface 48 of the central member 24 preferably engages the interior surface of the toe wall 30 of the periphery member 22. The heel surface 50 of the central member 24 preferably engages the heel wall 32 of the periphery member 22. The top surface 46 preferably creates the top line of the club head 20. The flange 52 extends from the top surface 46 outward over the forward surface 42 thereby creating a top cover for securing the face plate 26. The face plate 26 is also secured within a ledge 60 of the periphery member 22.

[0054] The face plate 26 is preferably composed of a lightweight material. The lightweight material has a density that is preferably lower than the periphery member material. Such lightweight materials include titanium materials, stainless steel, amorphous metals and the like. Such titanium materials include pure titanium and titanium alloys such as 6-4 titanium alloy, 6-22-22 titanium alloy, 4-2 titanium alloy, SP-700 titanium alloy (available from Nippon Steel of Tokyo, Japan), DAT 55G titanium alloy available from Diado Steel of Tokyo, Japan, Ti 10-2-3 Beta-C titanium alloy available from RTI International Metals of

Ohio, and the like. The face plate 26 is preferably manufactured through casting, forging, forming, machining, powdered metal forming, metal-injection-molding, electro-chemical milling, and the like.

[0055] The face plate 26 has an interior surface 56, which preferably engages the forward surface 42 of the central member 24, and an exterior surface 54 which preferably has scorelines (not shown) thereon. The face plate preferably has a thickness that ranges from 0.040 inch to 0.250 inch, more preferably from 0.06 inch to 0.130 inch, and most preferably 0.075 inch.

[0056] The club head 20 preferably has a total volume that ranges from 40.0 cm^3 to 60.0 cm^3 , more preferably from 45.0 cm^3 to 55.0 cm^3 , and most preferably 50.8 cm^3 . The club head 20 preferably has a mass that ranges from 240 grams to 270 grams, more preferably from 245 grams to 260 grams, and most preferably 253 grams.

[0057] The periphery member 22 preferably has a total volume that ranges from 10.0 cm^3 to 32.0 cm^3 , more preferably from 15.0 cm^3 to 20.0 cm^3 , and most preferably 18.8 cm^3 . The periphery member 22 preferably has a mass that ranges from 100 grams to 240 grams, more preferably from 150 grams to 200 grams, and most preferably 185

grams.

[0058] The central member 24 preferably has a total volume that ranges from 7.0 cm^3 to 35.0 cm^3 , more preferably from 15.0 cm^3 to 30.0 cm^3 , and most preferably 28.0 cm^3 . The central member 24 preferably has a mass that ranges from 9 grams to 70 grams, more preferably from 25 grams to 60 grams, and most preferably 45 grams.

[0059] The face plate 26 preferably has a total volume that ranges from 4.0 cm^3 to 8.0 cm^3 , more preferably from 4.5 cm^3 to 6.0 cm^3 , and most preferably 5.3 cm^3 . The face plate 26 preferably has a mass that ranges from 15 grams to 50 grams, more preferably from 20 grams to 30 grams, and most preferably 24 grams.

[0060] FIGS. 13–20 illustrate an iron golf club head in accordance with a second embodiment of the present invention 20'. The iron golf club head 20' includes a periphery member 22' composed of a material having a density greater than 7.86 g/cm^3 , a central member 24' composed of a non-metal material, and a face plate 26 composed of a metal material having a lower density than the material of the periphery member 22'.

[0061] The periphery member 22' is similar to the periphery member 22 of the first embodiment and has a sole wall

28, a toe wall 30, a heel wall 32, and a hosel 34 with a bore 36 for receiving a shaft. In addition, the periphery member 22' has a top wall 62, which extends from an upper end of the toe wall 30 to an upper end of the heel wall 32. The top wall 62, sole wall 28, toe wall 30 and heel wall 32 define an opening 64 through the periphery member 22'. The periphery member 22' has similar dimensions for sole wall 28, toe wall 30, and heel wall 32 as periphery member 22 of the club head 20 of the first embodiment.

[0062] The periphery member 22' provides the club head 20' with a greater moment of inertia due to its relatively large mass at the periphery of the club head 20'. Further, mass attributable to the sole wall 28 lowers the center of gravity of the club head 20' to promote a higher trajectory during ball striking. The periphery member 22' is preferably 15% to 50% of the volume of the club head 20' and preferably 50% to 80% of the mass of the club head 20'.

[0063] The central member 24' is composed of a non-metal material, such as a bulk molding compound, sheet molding compound, thermosetting material or thermoplastic material. The central member 24' supports the face plate 26 and acts to reduce vibrations of the club head 20' during ball striking. The central member 24' is preferably 25% to

75% of the volume of the club head 20' and preferably 10% to 30% of the mass of the club head 20'.

[0064] The central member 24' preferably has a body portion 38', a recess 40', a forward surface 42, a rear surface 43, a sole surface 44, a top surface 46, a toe surface 48, and a heel surface 50. The recess 40' is formed in the rear surface 43 of the body portion 38' and may have any of a number of suitable configurations. The body portion 38' preferably tapers upward from the sole surface 44.

[0065] The central member 24' is disposed in the opening 64 of the periphery member 22', with the sole surface 44 contacting an interior surface of the sole wall 28 of the periphery member 22'. The toe surface 48 of the central member 24' preferably engages the interior surface of the toe wall 30 of the periphery member 22'. The heel surface 50 of the central member 24' preferably engages the heel wall 32 of the periphery member 22'. The top surface 46 preferably engages the interior surface of the top wall 62 of the periphery member 22'.

[0066] The face plate 26 is also disposed in the opening 64 of the periphery member 22'. The periphery member 22' is preferably swaged to secure the face plate 26 in the opening 64. Alternatively, the face plate 26 may be

welded to the periphery member 22' or secured in place by an adhesive. The face plate 26 has an interior surface 56, which preferably engages the forward surface 42 of the central member 24', and an exterior surface 54, which preferably has scorelines 55 formed thereon. As described above, the face plate 26 is composed of a lightweight material and preferably has a thickness that ranges from 0.040 inch to 0.250 inch, more preferably from 0.060 inch to 0.130 inch, and most preferably about 0.075 inch.

[0067] FIGS. 9–12 illustrate the axes of inertia through the center of gravity of the golf club head. The axes of inertia are designated X, Y and Z. The X axis extends from rear of the golf club head 20 through the center of gravity, CG, and to the face plate 26. The Y axis extends from the heel end 75 of the golf club head 20 through the center of gravity, CG, and to the toe end 70 of the golf club head 20. The Z axis extends from the sole wall through the center of gravity, CG, and to the top line 80.

[0068] As defined in *Golf Club Design, Fitting, Alteration & Repair*, 4th Edition, by Ralph Maltby, the center of gravity, or center of mass, of the golf club head is a point inside of the club head determined by the vertical intersection of two or more points where the club head balances when sus–

pended. A more thorough explanation of this definition of the center of gravity is provided in *Golf Club Design, Fitting, Alteration & Repair*.

[0069] The center of gravity and the moment of inertia of a golf club head 20, 20' are preferably measured using a test frame (X^T, Y^T, Z^T), and then transformed to a head frame (X^H, Y^H, Z^H). The center of gravity of a golf club head 20 may be obtained using a center of gravity table having two weight scales thereon, as disclosed in co-pending U.S. Patent Application Number 09/796,951, filed on February 27, 2001, entitled High Moment Of Inertia Composite Golf Club, and hereby incorporated by reference in its entirety. If a shaft is present, it is removed and replaced with a hosel cube that has a multitude of faces normal to the axes of the golf club head. Given the weight of the golf club head, the scales allow one to determine the weight distribution of the golf club head when the golf club head is placed on both scales simultaneously and weighed along a particular direction, the X, Y or Z direction.

[0070] In general, the moment of inertia, I_{zz} , about the Z-axis for the golf club head 20, 20' preferably ranges from 2200 g-cm² to 3000 g-cm², more preferably from 2400 g-cm² to 2700 g-cm², and most preferably from 2472 g-cm² to

2617 g-cm². The moment of inertia, I_{yy} , about the Y-axis for the golf club head 20 preferably ranges from 400 g-cm² to 700 g-cm², more preferably from 500 g-cm² to 600 g-cm², and most preferably from 530 g-cm² to 560 g-cm². The moment of inertia, I_{xx} , about the X-axis for the golf club head 20 preferably ranges from 2450 g-cm² to 3200 g-cm², more preferably from 2500 g-cm² to 2900 g-cm², and most preferably from 2650 g-cm² to 2870 g-cm².

[0071] For comparison, the new BIG BERTHA®5-iron from Callaway Golf Company has a moment of inertia, I_{zz} , of 2158 g-cm², a moment of inertia, I_{yy} , of 585 g-cm², and a moment of inertia, I_{xx} , of 2407 g-cm².

[0072] From the foregoing it is believed that those skilled in the pertinent art will recognize the meritorious advancement of this invention and will readily understand that while the present invention has been described in association with a preferred embodiment thereof, and other embodiments illustrated in the accompanying drawings, numerous changes, modifications and substitutions of equivalents may be made therein without departing from the spirit and scope of this invention which is intended to be unlimited by the foregoing except as may appear in the follow-

ing appended claims. Therefore, the embodiments of the invention in which an exclusive property or privilege is claimed are defined in the following appended claims.